


#### Specification

		Model		B8CA-CE
Lighting system	Voltage (V)			230 *1
	Frequency (Hz)			50 / 60
		Input Current (A)		3.75 (230V,800W)
		Туре		LED
		Dimming Control		3 Stages : 800W / 600W / 400W
	ᡖ	Total Luminous Flux (Im) *2		110,000 (800W)
	Lamp			90,000 (600W)
				67,000 (400W)
		Outside Temperature (°C)		-10 to 40
	Mast	Mast Type		Telescopic Aluminum Mast
	St	Mast Operating		Hand Operation
	Cart	Tire		300mm External Diameter Pneumatic Tire
		Tire pressure (kPa)		245~297 (35.5~42.6PSI)
		Brake		One Step Foot Brake
		Outrigger		3 Support Outriggers
	Dimension	Operating (L x W x H) (mm)		1325 x 1300 x 1870-3200
		Storage (L x W x H)(mm)	Balloon	200 x 220 x 690
			Cart	1025 x 700 x 845
	Weight	Balloon (kg)		10.8
		Cable (kg)		1.4
	量	Mast (kg)		2.2
		Cart (kg)		37.5
	Total Weight (kg)			51.9
Appropriate Generator			•	870W and above

- \*1 Voltage 90-240V are available when power plugs are changed.
  \*2 LED chips differ from one case to the next on the production process, they have their own brightness and color temperature.

   All features and specifications are subject to change without notice.

#### Light coverage



### **LIGHT BOY EUROPE AB**

Södra Industrigatan 3, port 17 SE-274 30 Skurup Sweden Phone: +46 70 864 8810 Email: contact@light-boy.eu www.light-boy.eu



**B8CA** LED800W balloon, Assemble Cart





balloon lights are powerful but glare-free, providing optimal visibility for the crews.

## **LED Lamp Guard** ■

Light assembly is covered by special material. The material is same as glass covers of airplanes.



### **Gas Shock Absorbers**

The mast is designed to be retracted slowly so that the mast will not fall rapidly when released. This feature ensures the safety of the operator and around.



### Reverse Handle Mechanism

# Steerable Cart Design **■**

Steerable design guarantees operational flexibility. Reverse handle mechanism also maximises the force flow. These ensure a high degree of maneuverability.

### Foot Brake **■**

The one step foot brake



### Outriggers **■**

The cart is supported by three outriggers which stabilise the unit during the operation.



### **Compact assembable** disassemblable structure

The cart can be disassembled in a minute and placed on a bed of truck.









4 Compact storage.





# **Comparison with conventional light tower**

LIGHT BOY balloon lighting system provides powerful glare-free lighting. The system provides diffused illuminance that eliminates shadows, improves operator job awareness, and curtails glare to on-coming automotive traffic.



### **Conventional Light**









Highway maintenance

Railway possession

**Event**